

フランジ付リニアベアリング

—シングルタイプ—

dr	許容差	D		L	D1	T	d	d1	H1	P.C.D	K	F	A	偏芯	直角度	基本定格荷重		質量(g)		
		許容差	許容差													C(動)N	Co(静)N	丸フランジ	角フランジ	二面フランジ
6		12	0	19	28	5	3.5	6	3.1	20	22	-	20			206	265	24	18	21
8		15	-0.013	24	32					24	25	-	24			274	392	37	29	33
10	0	19		29	40					29	30	-	29	0.012	0.012	372	549	72	52	64
12	-0.009	21	0	30	42	6	4.5	7.5	4.1	32	32	-	32			510	784	76	57	68
13		23	-0.016	32	43					33	34	-	33			510	784	88	72	81
16		28		37	48					38	37	22	31			774	1,180	120	104	112
20		32	0	42	54	8	5.5	9	5.1	43	42	24	36			882	1,370	180	145	167
25	0	40	-0.019	59	62					51	50	32	40	0.015	0.015	980	1,570	340	300	325
30	-0.010	45		64	74	10	6.6	11	6.1	60	58	35	49			1,570	2,740	470	375	388
35	0	52	0	70	82					67	64	38	55			1,670	3,140	650	560	575
40		60	-0.022	80	96	13	9	14	8.1	78	75	45	64	0.020	0.020	2,160	4,020	1,060	880	913
50	-0.012	80		100	116					98	92	56	80			3,820	7,940	2,200	2,000	2,037

注:カッコ内は互換性品

注文例 Catalog No.
FLT8