

# フランジ付リニアベアリング

—ロングスリーブタイプ—

Catalog No.						D		L		D1	T	d	d1	H1	P.C.D	K	F	A	偏芯	直角度	
品名						dr	許容値	許容値	許容値												
丸フランジ	角フランジ		二面フランジ			6		15		50											
SUJ2	SUS440C	SUJ2	US440C	SUJ2	US440C	8	0	19	0	70											
						10	-0.009	23	-0.021	80											0.020
						12		26		85											
FLDL	MFLDL	FLDLK	MFLDLK	FLDLT	MFLDLT	16		32		100	±0.3										
(LHKRL)		(LHKSL)		(LHKCL)		20	0	40	0	120											
						25	-0.010	45	-0.025	165											0.025
						30		52	0	180											
									-0.030												

注:①カッコ内は互換性品

②FLDL6.8、FLDLK6.8、FLDLT6.8、MFDL6.8、MFLDLK6.8、MFLDLT6.8はグリースニップルなし。

dr	基本定格荷重		質量(g)		
	C(動)N	Co(静)N	丸フランジ	角フランジ	二面フランジ
6	324	530	70	60	—
8	431	784	140	120	—
10	588	1,100	210	190	—
12	657	1,200	250	230	—
16	1,230	2,350	420	380	390
20	1,400	2,740	760	720	730
25	1,560	3,140	1,250	1,170	1,180
30	2,490	5,490	1,640	1,550	1,570

注文例 Catalog No.

FLDL20