

フランジ付リニアベアリング

—ロングスリーブタイプ—

Catalog No.						D		L		ℓ	D1	T	d	d1	H1	P.C.D	K	F	A	偏芯	直角度							
品名						dr	許容値	許容値	許容値																			
丸フランジ		角フランジ		二面フランジ		6		15		50																		
SUJ2	SUS440C	SUJ2	US440C	SUJ2	US440C	8	0	19	0	70											0.020	0.020						
FLDLB (LHKIRL)	MFLDLB	FLDLKB (LHKISL)	MFLDLKB	FLDLTB (LHKICL)	MFLDLTB	10	-0.009	23	-0.021	80	±0.3																	
						12		26		85																		
						16		32	0	100																		
						20	0	40	-0.025	120																		
						25	-0.010	45		165																		
						30		52	0	180																		
														-0.030														

注:①カッコ内は互換性品

②FLDLB6.8、FLDLKB6.8、FLDLTB6.8、MFLDLB6.8、MFLDLKB6.8、MFLDLTB6.8はグリースニップルなし。

dr	基本定格荷重		質量 (g)		
	C(動)N	Co(静)N	丸フランジ	角フランジ	二面フランジ
6	324	530	70	60	—
8	431	784	140	120	—
10	588	1,100	210	190	—
12	657	1,200	250	230	—
16	1,230	2,350	420	380	390
20	1,400	2,740	760	720	730
25	1,560	3,140	1,250	1,170	1,180
30	2,490	5,490	1,640	1,550	1,570

注文例 Catalog No.

FLDLB20