

フランジ付リニアベアリング

—ロングスリーブセンターフランジタイプ—

Catalog No.						D		L		ℓ	D ₁	T	d	d ₁	H ₁	P.C.D	K	F	A	偏芯	直角度	
品名						dr	許容値	許容値	許容値													
丸フランジ		角フランジ		二面フランジ		6		15		50												
SUJ2	SUS440C	SUJ2	SUS440C	SUJ2	SUS440C	8	0	19	0	70										0.020	0.020	
FLDLC (LHKMRL)	MFLDLC	FLDLKC (LHKMSL)	MFLDLKC	FLDLTC (LHKMLL)	MFLDTC	10	-0.009	23	-0.021	80	±0.3	17	32	5	3.5	6	3.1	24	25	—	—	
						12		26		85		22	39	6	4.5	7.5	4.1	29	30	—	—	
						16		32	0	100		27	43	6	4.5	7.5	4.1	33	34	—	—	
						20	0	40	-0.025	120		28	46	6	4.5	7.5	4.1	36	35	—	—	
						25	-0.010	45		165		35	54	8	5.5	9	5.1	43	42	24	36	
						30		52	0 -0.030	180		40	62	8	5.5	9	5.1	51	50	32	40	
											55	74	10	6.6	11	6.1	60	58	35	49		
											61	82	10	6.6	11	6.1	67	64	38	55		

注:①カッコ内は互換性品

②FLDLC6.8、FLDLKC6.8、FLDLTC6.8、MFLDLC6.8、MFLDLKC6.8、MFLDLTC6.8グリースニップルなし。

dr	基本定格荷重		質量 (g)		
	C (動) N	Co (静) N	丸フランジ	角フランジ	二面フランジ
6	324	530	70	60	—
8	431	784	140	120	—
10	588	1,100	210	190	—
12	657	1,200	250	230	—
16	1,230	2,350	420	380	390
20	1,400	2,740	760	720	730
25	1,560	3,140	1,250	1,170	1,180
30	2,490	5,490	1,640	1,550	1,570

注文例 Catalog No.

FLDLKC20