

フランジ付リニアベアリング

—ロングスリーブセンターフランジタイプ—

Catalog No.						D		L		ℓ	D ₁	T	d	d ₁	H ₁	P.C.D	K	F	A	偏芯	直角度						
品名						dr	許容値	許容値	許容値																		
丸フランジ		角フランジ		二面フランジ		6		15		50																	
SUJ2	SUS440C	SUJ2	SUS440C	SUJ2	SUS440C	8	0	19	0	70										0.020	0.020						
FLDLC (LHKMRL)	MFLDLC	FLDLKC (LHKMSL)	MFLDLKC	FLDLTC (LHKMLL)	MFLDTC	10	-0.009	23	-0.021	80	±0.3																
						12		26		85																	
						16		32		100																	
						20	0	40	-0.025	120																	
						25	-0.010	45		165																	
						30		52	0 -0.030	180																	

注:①カッコ内は互換性品

②FLDLC6.8、FLDLKC6.8、FLDLTC6.8、MFLDLC6.8、MFLDLKC6.8、MFLDLTC6.8グリースニップルなし。

dr	基本定格荷重		質量 (g)		
	C (動) N	Co (静) N	丸フランジ	角フランジ	二面フランジ
6	324	530	70	60	—
8	431	784	140	120	—
10	588	1,100	210	190	—
12	657	1,200	250	230	—
16	1,230	2,350	420	380	390
20	1,400	2,740	760	720	730
25	1,560	3,140	1,250	1,170	1,180
30	2,490	5,490	1,640	1,550	1,570

注文例 Catalog No.

FLDLKC20