

Catalog No.		D		L		D1	T	P.C.D	K	取付		グリースニップル
品名	dr 許容値		許容値		許容値					S1	S2	
FLWT (丸形)(FLW)	6		20	0	46	38	7	30	30	M5	M4	—
FLWTK (角形)	8		24	-0.021	56	44	7	35	35	M5	M4	
FLWTG (丸形・ニップル付)	10	0	30		68	52	8	42	42	M5	M4	
FLWTKG (角形・ニップル付)	12	-0.009	34		70	54	8	45	44	M5	M4	
ステンレスベアリング	13		34	0	70	54	8	45	44	M5	M4	
MFLWT (丸形)	16		42	-0.025	88	72	9	58	58	M8	M6	
MFLWTK (角形)	20	0	48		98	78	10	64	62	M8	M6	
MFLWTG (丸形・ニップル付)	25	-0.010	58	0	134	90	11	76	72	M8	M6	
MFLWTKG (角形・ニップル付)	30		65	-0.030	144	104	12	86	84	M10	M8	
	40	0	84	-0.035	178	124	14	106	100	M10	M8	

dr	基本定格荷重		質量 (g)	
	C (動) N	Co (静) N	丸フランジ	角フランジ
6	324	530	50	50
8	431	784	90	90
10	588	1,100	160	150
12	813	1,570	190	170
13	813	1,570	200	180
16	1,230	2,350	370	340
20	1,400	2,740	510	460
25	1,560	3,140	1,020	940
30	2,490	5,490	1,440	1,300
40	3,430	8,040	2,750	2,560

注文例 Catalog No.  
FLWT6