

# フランジ付リニアブロック

—軽量ロングスリーブタイプ—

Catalog No.		L	D	C	D0	D1	T	B	P.C.D	K	S	取付			
品名	dr 許容値											許容値	S1	S2	
FLWL (丸形)	16	0 -0.009	150	45	0	22	44	80	11	20	60	60	7	M8	M6
	20	0	150	50	-0.025	24	49	90	12	20	70	66	9	M10	M8
FLWLK (角形)	200		30												
FLWL (丸形)	25	0	200	60	0	30	59	100	15	30	80	74	11	M12	M10
			FLWLKB (角形・インロー)							250					
ステンレスベアリング		-0.010	200	70	-0.030	36	69	120	18	30	100	90	11	M12	M10
MFLWL (丸形)	250		40												
MFLWLK (角形)	300		50												
MFLWL (丸形)	40	0	250	90	0	40	89	160	20	40	130	126	14	M14	M12
			MFLWLKB (角形・インロー)							300					
MFLWLKB (角形・インロー)	50	-0.012	300	120	-0.035	40	119	190	20	50	160	150	14	M14	M12
			350							60					

※フェルトシールも両端に取付けられる構造になっています。(ダブルシール型)

dr	L	基本定格荷重		質量 (Kg)	
		C (動) N	Co (静) N	丸フランジ	角フランジ
16	150	1,230	2,350	0.5	0.48
20	150	1,400	2,740	0.6	0.58
	200			0.8	0.78
25	200	1,560	3,140	1.0	0.97
	250			1.6	1.57
30	200	2,490	5,490	1.5	1.45
	250			2.0	1.95
	300			2.5	2.45
40	250	3,430	8,040	4.0	3.93
	300			4.5	4.43
50	300	6,080	15,900	8.0	7.92
	350			8.5	8.42

注文例 Catalog No.  
FLWL20-200