

リニアブロック

—シングルタイプ—

Catalog No.				h	W ₁	W	L	H	H ₁	t	W ₂	L ₁	W ₃	M	d	ℓ	F	
品名		dr	許容値															
SUJ2		SUS440C		10	13	20	40	35	26	22		28	21	6			19	
—	ニップル付	—	ニップル付	12	15	21	42	36	28	24	8	30.5	26	5.75	M5	4.3	12	21
				13		22	44	39	30	25		33		5.5				23
LBB (LHBB)	LBBG	MLBB	LBBSG	16	19	25	50	44	37	32	9	36	34	7	M6	5.2		24
				20	21	27	54	50	41	35	11	40	40					28
				25	26	38	76	67	51	45	12	54	50	11	M8	7	18	36
				30	30	39	78	72	57	50	15	58	58	10				38
40	40	51	102	90	75	65	22	80	60	11	M10	9	25	58				

注:カッコ内は互換性品

dr	基本定格荷重		質量 (kgf)
	C(動)N	Co(静)N	
10	372	549	0.10
12	510	784	0.11
13	510	784	0.12
16	774	1,180	0.17
20	882	1,370	0.21
25	980	1,570	0.51
30	1,570	2,740	0.60
40	2,160	4,020	1.20

注文例 Catalog No.
LBB20